

Technical Specification

Model No.: GF Series




Size: 120*180*30mm

1. Introduction:

- HM87 is an EU-standard pluggable OPS computing module for smart boards and commercial displays.
- It adopts HM87 chipset, supports Intel 4th Gen Core mobile CPUs with integrated Intel HD Graphics 4600.
- It connects to displays via standard 80-pin OPS gold finger connector.
- With rich I/O ports and wireless expansion, it runs Windows 7/10, supporting fast replacement and stable long-time operation.

2. Main Features


- HM87 chipset, supports Intel® 4th Gen Core mobile CPUs; Intel HD Graphics 4600, HDMI up to 4K@30Hz
- Standard 80-pin OPS gold finger, EU compliant, pluggable design for easy installation & maintenance
- Single-channel SO-DIMM DDR3 1333/1600MHz, max 8GB; dual storage: 1×M.2 + 1×M.2-2280 SATA SSD
- Full I/O: 3×USB3.0, 3×USB2.0, HDMI, VGA, RTL8111H Gigabit LAN, MIC In, Line Out
- eM.2 2230 slot for 2.4G/5G WiFi5/WiFi6+BT, paired with dual-band antennas
- fPower button & one-key OS recovery button; Power LED and HDD activity LED
- HDMI & USB signals available via 80Pin OPS connector; DC input:12V~19V
- Operation system:Windows7/10



3. Specifications

Model	GF Series
CPU	Support Intel ® 4th generation core mobile CPU
Chipset	HM87/HM86
RAM	Single channel SO-DIMM DDR3, 1333/1600MHz Maximum To 8GB
SSD	1×Msata 1×M.2-2280 SATA
Graphics	Intel HD graphics 4600
USB	3×USB3.0 3×USB2.0
Audio	1×MIC In (Pink) 1×Line Out (Green)
HDMI	1×HDMI (Max. support resolution ratio 3840x2160@30Hz)
VGA	1×VGA (Max. support resolution ratio 1920x1080@60Hz)
LAN	1×RJ45 (RTL8111 hgigabit LAN)
LED Light	1xHDD LED (System running normally: red light blinking) 1xPower LED (System running normally: green light blinking)
Antenna	2×2.4G/5G Dual antenna
Power Button	1xPower button
Resetore	1xResetore
WLAN	1×M.2 2230 2.4G/5G/6G+BT (Wifi5、Wifi6 optional)
80Pin OPS Interface	1×HDMI (Max. support resolution ratio 3840x2160@30Hz) 1×USB3.0 2×USB2.0 12V~19V
Windows	Windows 7/10
Power Supply	TRNF DC IN, Input Voltage 12V~19V
Operation	Temperature: -10°C~50°C; Humidity: 10%~90%RH
Storage	Temperature: -20°C~60°C; Humidity: 0%~90%RH
Structure Dimension (L×W×T)	120mm×180mm×30mm

4. I/O Interfaces



5. Product Advantages

- Ultra-low resistance transistors for CPU power supply, stable for 24/7 continuous operation
- Optimized PCB layout & air channel, excellent heat dissipation to avoid thermal throttling
- Flexible sub-card options to satisfy various project requirements
- Supports watchdog, power-on boot, remote wake-up and hardware monitoring for centralized management
- Great compatibility with education, meeting and digital signage software

6. Disclaimer

- Due to product configuration and manufacturing process, the actual body size and weight may vary. Please refer to the real product.
- Pictures in this specification are for illustration only. The appearance, color, dimension and other details of the delivered product may differ slightly. Please refer to the real product.
- To ensure accurate descriptions, we reserve the right to revise text, images and other contents of this specification to match the actual product performance and specifications without prior notice.